

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 02/27/2003

Reviewed on 02/24/2003

1 Identification of substance

Trade name: MRO GLOSS WHITE
Product code: 0006201413
Manufacturer/Supplier: SEYMOUR OF SYCAMORE
 917 Crosby Avenue
 Sycamore, IL 60178
 (815)-895-9101
Information department: Health & Safety Department
Emergency information: CHEMTEL 1-800-255-3924



2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	acetone	☒ Xi, ☒ F; R 11-36-66-67	17.81%
74-98-6	propane	☒ F+; R 12	15.74%
13463-67-7	titanium dioxide	☒ Xi; R 37	11.98%
106-97-8	n-butane	☒ F+; R 12	9.24%
7727-43-7	barium sulphate, natural	☒ Xi; R 37	5.01%
108-10-1	methyl isobutyl ketone	☒ Xn, ☒ F; R 11-20-36/37-66	4.87%
2807-30-9	Glycol Ether EP	☒ Xi; R 10-36/37/38	4.81%
110-19-0	isobutyl acetate	☒ F; R 11-66	4.79%
107-87-9	Methyl Propyl Ketone	☒ F; R 11	3.44%
1330-20-7	xylene (mix)	☒ Xn; R 10-20/21-38	2.4%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:



Xi Irritant
 F+ Extremely flammable

Physical and environmental dangers:

Warning! Pressurized container.
 Has a narcotizing effect.
 R 12 Extremely flammable.
 R 36/37 Irritating to eyes and respiratory system.
 R 67 Vapours may cause drowsiness and dizziness
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C,
 i.e. electric lights. Do not pierce or burn, even after use.
 Keep out of the reach of children.

NFPA ratings (scale 0 - 4): Health = 1
 Fire = 4
 Reactivity = 3

HMIS-ratings (scale 0 - 4): Health = 1
 Fire = 3
 Physical Hazard = 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Generally the product does not irritate the skin.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Consult a doctor if symptoms persist.

5 Fire fighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.
Protective equipment: No special measures required.

6 Accidental release measures

Personal safety precautions: Wear protective equipment. Keep unprotected persons away.
Environmental safety precautions: Do not allow product to reach sewage systems or ground water.
 Inform appropriate authorities in case of seepage into water course or sewage system.

(Contd. on page 2)
 USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 02/27/2003

Reviewed on 02/24/2003

Trade name: MRO GLOSS WHITE

(Contd. of page 1)

**Measures for cleaning/
collecting:**

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage**Safe handling
information:**

Handle carton and cans with care.

Fire/explosion protection:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Storage requirements:

Observe official regulations on storing packagings with pressurized containers. Consult with your local authorities.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:**Components with limit values that require monitoring at the workplace:****67-64-1 acetone**

REL 2400 mg/m³, 1000 ppm
REL 590 mg/m³, 250 ppm
TLV Short-term value: 1782 mg/m³, 750 ppm
Long-term value: 1188 mg/m³, 500 ppm
BEI

74-98-6 propane

REL 1800 mg/m³, 1000 ppm
REL 1800 mg/m³, 1000 ppm
TLV 4508 mg/m³, 2500 ppm

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
TLV 1900 mg/m³, 800 ppm

7727-43-7 barium sulphate, natural

REL 15*; 5** mg/m³
*Total dust **Respirable fraction
REL 10*; 5** mg/m³
*Total dust **Respirable fraction
TLV 10 mg/m³
(e)

108-10-1 methyl isobutyl ketone

REL 410 mg/m³, 100 ppm
REL Short-term value: 300 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm
TLV Short-term value: 307 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm
BEI

110-19-0 isobutyl acetate

REL 700 mg/m³, 150 ppm
REL 700 mg/m³, 150 ppm
TLV 713 mg/m³, 150 ppm

107-87-9 Methyl Propyl Ketone

REL 700 mg/m³, 200 ppm
REL 530 mg/m³, 150 ppm
TLV Short-term value: 881 mg/m³, 250 ppm
Long-term value: 705 mg/m³, 200 ppm

1330-20-7 xylene (mix)

REL 435 mg/m³, 100 ppm
REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm
(o-, m-, & p-isomers)
TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

**Protective hygienic
measures:**

Keep away from foodstuffs, beverages, and animal feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

(Contd. on page 3)
USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 02/27/2003

Reviewed on 02/24/2003

Trade name: MRO GLOSS WHITE

(Contd. of page 2)

Breathing equipment: For episodes of brief exposure, use a respiratory filter device. In cases of intensive or longer exposures, use a respiratory protective device that is independent of circulating air.

Protection of hands: Use suitable respiratory protective device in case of insufficient ventilation. Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties:

General Information:

Form:	Aerosol
Color:	According to trade name description in section 1.
Odor:	Solvent
Boiling point/Boiling range:	-44°C (-47°F)
Flash point:	-19°C (-2°F)
Ignition temperature:	365.0°C (689°F)
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Heating may cause an explosion. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	13.0 Vol %
Vapor pressure at 20°C (68°F):	8300.0 hPa (6226 mm Hg)
Density:	Not determined.
Specific Gravity:	Between 0.77 and 0.90 (Water equals 1.00)
VOC content:	0.46 kg/l / 3.85 lb/gl
VOC in weight percent (less acetone):	46.1 %
Solids content:	35.1 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Dangerous reactions: No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect.

Primary effect on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Other information: This product does not contain any chlorinated solvents or lead. No specific ecological data is available for this product.

Aquatic toxicity: Harmful to aquatic organisms.
Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Do not dispose with household garbage. Do not allow product to reach sewage system.

14 Transport information:

Hazard class:	2.1
Identification number:	N/A
Label:	2.1
ADR/RID class:	2 5TF Gases
UN-Number:	1950
IMDG Class:	2
Packaging group:	II
EMS Number:	F-D,S-U
Marine pollutant:	No
ICAO/IATA Class:	2.1

(Contd. on page 4)
USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 02/27/2003

Reviewed on 02/24/2003

Trade name: MRO GLOSS WHITE

(Contd. of page 3)

Propper shipping name: Aerosols, Flammable
Consumer Commodity ORM-D

15 Regulations**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

100-41-4 ethyl benzene

TSCA (Toxic Substances Control Act):

67-64-1 acetone

74-98-6 propane

13463-67-7 titanium dioxide

106-97-8 n-butane

7727-43-7 barium sulphate, natural

108-10-1 methyl isobutyl ketone

2807-30-9 Glycol Ether EP

110-19-0 isobutyl acetate

107-87-9 Methyl Propyl Ketone

1330-20-7 xylene (mix)

100-41-4 ethyl benzene

8002-43-5 Soya Lecithin

22464-99-9 solid zirco drier

64742-47-8 Mineral Spirits

1317-65-3 Calcium Carbonate

PROPOSITION 65 Chemicals known to cause cancer:

None of the ingredients in this product are listed.

PROPOSITION 65 Chemicals known to cause reproductive toxicity:

None of the ingredients in this product are listed.

Canadian WHMIS: This product has been classified according to the Controlled Product Regulations and the MSDS contains all the necessary information required by the CPR.

Class B, D5---Flammable Aerosols

EPA: A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

67-64-1	acetone	D
110-19-0	isobutyl acetate	D
1330-20-7	xylene (mix)	D
100-41-4	ethyl benzene	D

IARC: Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

13463-67-7	titanium dioxide	3
1330-20-7	xylene (mix)	3

ACGIH TLVs: A1-designates a confirmed human carcinogen.
A2-designates a suspected human carcinogen.
A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
110-19-0	isobutyl acetate	A4
1330-20-7	xylene (mix)	A4

NIOSH:

13463-67-7 titanium dioxide

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 5)
USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 02/27/2003

Reviewed on 02/24/2003

Trade name: MRO GLOSS WHITE

Contact: Craig Swafford
Regulatory Affairs

(Contd. of page 4)

USA